



CPA Belt driven Rotary Screw Compressors From 7.5 To 20 HP

CPA Base

A design where everything is rational. Particular care has been taken to resolving air circulation problems inside the machine. The use of quality reliable components allows optimal performance form an excellent screw air end.




CPA series: Floor Mounted

Technology	Screw
Use	Continuous
Air quality	Standard
Noise level	Silent



User benefits

Low noise levels	Easy and fast maintenance	Advanced control and monitoring	Built to last
Insulation foam, deflectors and anti-vibration pads assure low noise levels.	Enabled by good positioning of service items: belts, oil and filters.	Accurate control to work at the most optimal conditions.	Designed for continuous duty and very hard working conditions.



Type	l/m	m ³ /h	cfm	HP	kW	bar	psi	volt	L x W x H (mm)	Start	dB(A)	connection gas	Kg
CPA 7,5/8	805	48	28	7,5	5,5	8	116	380V/3ph/50Hz 400V/3ph/50Hz	980 x 615 x 1040	sds	65	3/4	255
CPA 7,5/10	629	38	22	7,5	5,5	10	145		980 x 615 x 1040	sds	65	3/4	255
CPA 7,5/13	517	31	18	7,5	5,5	13	189		980 x 615 x 1040	sds	65	3/4	255
CPA 10/8	1129	68	40	10	7,5	8	116		980 x 615 x 1040	sds	65	3/4	260
CPA 10/10	1016	61	36	10	7,5	10	145		980 x 615 x 1040	sds	65	3/4	260
CPA 10/13	785	47	28	10	7,5	13	189		980 x 615 x 1040	sds	65	3/4	260
CPA 15/8	1603	96	57	15	11	8	116		980 x 615 x 1040	sds	66	3/4	275
CPA 15/10	1417	85	50	15	11	10	145		980 x 615 x 1040	sds	66	3/4	275
CPA 15/13	1166	70	41	15	11	13	189		980 x 615 x 1040	sds	66	3/4	275
CPA 20/8	1897	114	67	20	15	8	116		980 x 615 x 1040	sds	66	3/4	290
CPA 20/10	1689	101	60	20	15	10	145		980 x 615 x 1040	sds	66	3/4	290
CPA 20/13	1475	89	52	20	15	13	189		980 x 615 x 1040	sds	66	3/4	290